**IN THE CLAIMS:** 

Please revise the claims, as follows:

1. (Currently amended) A method of guaranteeing authenticity of an object, said object

including at least one of a chip having a first recording support and a second recording support,

said method comprising:

providing a sample of material obtainable only by at least one of chemical and physical

processes such that a measurable characteristic of said sample is random and not reproducible

and affixing said sample to said object;

using a reader to take a measurement of said characteristic of said sample, said

measurement becoming associating a number reproducibly associated to said sample by using a

specific reader; and

to allow for sample-reader combinations such that the number associated to said sample

is only essentially reproducible at a time of verification, recording said number on said object on

at least one of said first recording support and said second recording support.

2. (Canceled)

3. (Previously presented) The method according to claim 39, wherein said object comprises a

smart card.

4. (Original) The method according to claim 3, wherein said smart card incorporates a chip.

5-6. (Canceled)

S/N 09/397,503

7. (Previously presented) The method according to claim 1, further comprising:

forming at least one coded version of said number, said at least one coded version being obtained by a key signature, wherein said key signature includes using public key cryptography;

and

recording said at least one coded version on at least one of said first recording support

and said second recording support.

8. (Previously presented) The method according to claim 39, further comprising:

reading, by a reader, the sample in an imprecise manner, meaning that sequential readings

are not exactly the same as an initial reading of said sample, but collecting, at a time of

preparation of the object, much more information about said sample that will be contained by

decoding any of said coded version of that information,

wherein said object carries a chip and a recording of a digital representation of the full

information initially collected of the sample from the reader used at the time the object is

prepared.

9. (Original) The method according to claim 8, further comprising:

sending a result of the reader to a processor, which associates with the reading of the

sample said number;

sending said number to a second processor containing a secure hash function, details of

which are made public, and a secret part of said key signature, said key signature comprising a

S/N 09/397,503

public key signature, wherein said second processor computes a coded version of the hash of said

number appended with a predetermined, optional data; and

outputting said coded version to said chip.

10. (Original) The method according to claim 9, wherein upon introducing the object into a

second reader, a different reading of said sample occurs such that the first reader reads the

sample to deliver R(S) and the second reader reads the sample to deliver RO(SO), said method

further comprising:

determining by a comparator whether the readings by said first and second readers are

less than or equal to a predetermined threshold to accept the object, at least temporarily, as

authentic.

11. (Original) The method according to claim 10, further comprising:

reading said coded version by said chip and verifying said coded version against said

number by using a public part of the public key signature; and

if said number and said coded version read by said chip are compatible, accepting the

card as authentic.

12. (Original) The method according to claim 8, further comprising:

delivering by said reader an actual reading R(S) and delivering by a second reader an

original reading as RO(SO);

processing said readings by first and second processors to deliver N(R(S)) and N(R(S)),

respectively; and

S/N 09/397,503

determining by a comparator whether outputs from said first and second processors have

a value no more than a predetermined threshold, to temporarily accept the object as authentic.

13. (Original) The method according to claim 12, further comprising:

reading the coded version in said chip and verifying said coded version against said

number by using a public portion of a public key signature; and

if the information in said number and that read in said chip are compatible, accepting said

object as authentic.

14. (Previously presented) The method according to claim 39, further comprising:

sensing a degeneration of said sample.

15. (Original) The method according to claim 14, wherein said sensing includes comparing a

difference between an actual reading vector and an original reading vector against a threshold;

forwarding a result of the reader to a processor, which associates with the reading of said

sample a transformed vector K(NO(RO(SO))), where K is a transformation matrix; and

forwarding the transformed vector to a second processor including a secure hash

function, details of which are made public, and a secret part of a public key signature scheme.

16. (Original) The method according to claim 15, wherein said object includes a chip, and

wherein said second processor computes a coded version of the hash function of the transformed

vector appended with predetermined optional external data, to provide a coded number, said

coded number being put on said chip,

S/N 09/397,503

wherein upon introducing the card to a second reader, a predetermined different reading

of the sample is performed.

17. (Original) The method according to claim 16, wherein an actual reading made by a first

reader is transformed into a transformed vector KN, and wherein an original transformed vector

KN0 is delivered by a second reader, and

wherein the transformed vector, KN is compared against the original transformed vector

KNO by a comparator such that if the two transformed vectors have a value within a

predetermined closeness, the object is temporarily accepted as authentic.

18. (Previously presented) The method according to claim 17, further comprising:

reading by said chip the coded version and verifying said coded version against the

transformed vector using a public part of the public key signature; and

accepting the object as authentic if the transformed vector and the coded version read in

said chip are compatible.

19. (Previously presented) The method according to claim 39, wherein said object being

authenticated comprises a piece of paper.

20. (Previously presented) The method according to claim 39, wherein a sequence of data

associated with said sample, said sample, and certificates associated with said sample and said

data are precomputed.

S/N 09/397,503

21. (Previously presented) The method according to claim 20, wherein new data and its

certificate are computed dynamically.

22. (Previously presented) The method according to claim 39, wherein said key signature

includes using private key cryptography.

23. (Previously presented) The method according to claim 39, wherein said specific reader

captures information out of the sample by one of a scanning and globally.

24. (Currently amended) The method according to claim 39, wherein said sample includes at

least one of a an exposed face of a mineral sample and a an exposed face of a glass sample,

selectively covered by a carbon film and affixed to said object.

25. (Previously presented) The method according to claim 39, wherein said coded version of

said number includes at least one of optional data appended to said number and a hash of said

number with said optional data.

26. (Currently amended) The method according to claim 39, wherein data linked to the sample

of material is selectively changeable during at least one reading subsequent to an initial reading

of said sample at said time of production.

27. (Previously presented) The method according to claim 39, wherein said sample of material

is selectively changeable over time.

S/N 09/397,503

28. (Previously presented) The method according to claim 39, wherein said data is selectively

changeable when said sample is changed.

29. (Original) The method according to claim 20, wherein said data is selectively changeable

when said sample is changed.

30. (Previously presented) The method according to claim 39, wherein new data associated with

said sample and a certificate of said sample are computed dynamically.

31. (Previously presented) The method according to claim 39, wherein at a time of creation of

said object, said coded version of said number is stored in memory for later comparison when

said object is presented for authentication.

32. (Previously presented) The method according to claim 39, wherein a plurality of coded

versions of numbers are recorded into said object.

33. (Previously presented) A method of preventing cloning of an object, said method

comprising:

providing a sample of material obtainable only by at least one of chemical and physical

processes having a characteristic that samples obtained by said process are random and not

reproducible;

S/N 09/397,503

associating a number reproducibly to said sample by using a specific reader as an initial

measurement of said sample;

forming at least one coded version of said number by a public key signature; and

recording said number and at least one of said at least one encoded versions on said

object.

34. (Previously presented) A method of preventing imitation of a smart card, said method

comprising:

providing a sample of material obtainable only by at least one of chemical and physical

processes having a characteristic that samples obtained by said process are random and not

reproducible;

associating a number reproducibly to any said sample by using a specific reader as an

initial reading of said characteristic;

forming at least one coded version of said number by a public key signature; and

recording said number and at least one of said at least one coded version into an area of

said smart card.

35. (Previously presented) A system for guaranteeing authenticity of an object, said method

comprising:

a sample of material obtainable only by at least one of chemical and physical processes

having a characteristic that samples obtained by said process are random and not reproducible,

said sample being placed on said object;

S/N 09/397,503

means for associating a number reproducibly to any said sample by using a specific

reader, said specific reader providing an initial measurement of said characteristic and an initial

associated number:

means for forming at least one coded version of said initial associated number, said at

least one coded version being obtained by a public key signature; and

means for recording said number and said at least one coded version into an area of said

object.

36. (Previously presented) A signal-bearing medium tangibly embodying a program of

machine-readable instructions executable by a digital processing apparatus to perform a method

for computer-implemented guaranteeing of authenticity, said method comprising:

for a sample of material obtainable only by at least one of chemical and physical

processes such that the sample is random and not reproducible, associating a number

reproducibly to said sample by using a specific reader;

recording said number on a recording medium on an object;

forming at least one coded version of said number; and

recording said at least one coded version of said number on said recording medium of

said object.

37. (Previously presented) The method of claim 39, wherein said forming at least one coded

version of said number further comprises using additional information for said forming said

coded version, wherein said additional information comprises the date of issue of said object.

S/N 09/397,503

38. (Previously presented) The method of claim 39, wherein said forming at least one coded

version of said number further comprises using additional information for said forming said

coded version, wherein said additional information comprises the functionality of an application

of said object.

39. (Currently amended) A method of guaranteeing authenticity of an object that includes or

has attached thereto at least one of a chip with a recording support and another recording

support, said method comprising:

attaching to said object a first sample of material obtainable by at least one of a chemical

process and a physical process having a characteristic that samples generated by said process are

random and non-reproducible, said first sample being associated with a first number obtained by

reading said first sample using a first reader of a specific sort, said first number being long

enough to both:

carry enough information to detect any counterfeited second sample different

from said first sample but which second sample, when read with a reader of said specific sort,

would generate a second reading substantially identical to said first reading of said first sample;

and

contain as many digits as encryptions that are considered as safe at a time of

production and expected to be safe for some years to come afterward;

recording, on at least one of said recording supports, at said time of production, in an

exactly readable way, an exact value of said first number so that said first number can be

checked against a later reading made with any reader of said specific sort at each time of

S/N 09/397,503

verification of said object, thereby providing a first verification that verifies that a sample being

read at said verification of said object is indeed said first sample; and

forming, at said time of production, at least one encrypted version of said first number, at

least one of said encrypted versions of said first number being also recorded in an exactly

readable way on said object at said time of production, said at least one encrypted version of said

first number being obtained by a method from public key cryptography that is considered as safe

at said time of production and expected to be safe for some years to come afterward, said

recording of said at least one encrypted version thereby providing a second verification that

verifies at said verification that said encrypted version of said first number was generated by an

authorized party,

wherein information concerning said public key cryptography method is available so that

said second verification can be made by anyone of an intended public.

40. (Previously presented) The method of claim 39, wherein said first number is encrypted in

combination with further information, said further information and all encrypted versions of said

first number being also recorded in an exactly readable way on said object at said time of

production.

41. (Previously presented) The method of claim 39, further comprising:

forming at least one second encrypted version of said first number by a private key

cryptography encryption scheme; and

recording said at least one second encrypted version in an exactly readable manner on

said object.

S/N 09/397,503

42. (Previously presented) A method of guaranteeing authenticity of an object that includes or has attached thereto at least one of a chip with a first recording support and a second recording support, said method comprising:

attaching to said object a first sample of material obtainable by at least one of a chemical process and a physical process having a characteristic that samples generated by said process are random and non-reproducible, said first sample being associated with a first number obtained by first reading said first sample using a first reader of a specific sort to obtain a temporary first number and then extracting said first number from said temporary first number, using a statistical method, said first number being long enough to both:

from said first sample but which second sample, when read with a reader of said specific sort, would generate a second reading substantially identical to said first reading of said first sample; and

contain as many digits as encryptions that are considered as safe at a time of production and expected to be safe for some years to come afterward; and

forming, at said time of production, at least one encrypted version of said first number, at least one of said encrypted versions of said first number being also recorded in an exactly readable way on said object at said time of production on at least one of said first recording support and said second recording support, said at least one encrypted version of said first number being obtained by a method from public key cryptography that is considered as safe at said time of production and expected to be safe for some years to come afterward, said recording of said at least one encrypted version thereby providing a second verification that verifies at said S/N 09/397,503

verification that said encrypted version of said first number was generated by an authorized

party,

wherein:

information concerning said public key cryptography method is available so that

said second verification can be made by anyone of an intended public, and

upon reading a sample attached to said object at a time of verification, a reader of

said specific sort is to be used so that each later reading is substantially the same as an initial

reading at said time of production by said first reader and a statistical method sufficiently robust

to accommodate small changes in reading is to be used to produce a second number to be

compared with said first number for said first verification.

43. (Previously presented) The method of claim 42, wherein said first number is encrypted in

combination with further information, said further information and all encrypted versions of said

first number being also recorded in an exactly readable way on said object on at least one of said

first recording support and said second recording support at said time of production.

44. (Previously presented) The method of claim 42, further comprising:

forming at least one second encrypted version of said first number by a private key

cryptography encryption scheme; and

recording said at least one second encrypted version in an exactly readable manner on

said object on at least one of said first recording support and said second recording support.

S/N 09/397,503

45. (Previously presented) The method of claim 39, wherein said first number is converted into

and recorded in a base 3 number format.

46. (Previously presented) The method of claim 1, wherein said number is expressed as a vector

vk(S), said method further comprising:

reading said number a plurality of times by said reader to determine an average Ak of

said vector vk(S);

determining a small window Wk around said average Ak that defines a range of readings

considered as acceptable for said sample; and

recording said average Ak and said small window Wk on at least one of said first

recording support and said second recording support.

47. (Previously presented) The method of claim 1, wherein said process provides a sample that

becomes unreadable after an amount of time that is predetermined, said authenticity of said

object being thereby guaranteed only during a time shorter than said predetermined amount of

time.

48. (Previously presented) The method of claim 1, wherein said object comprises a container

having a contents therein, and said sample is attached to said container as a seal thereof, and an

opening of said container causes said sample to be altered in a manner that a subsequent reading

by a reader provides a reading different from said number, thereby an authenticity of said

contents is guaranteed when said subsequent reading agrees with said reading having been

recorded.

S/N 09/397,503

49. (Previously presented) The method of claim 1, wherein said process provides a sample that

degenerates over time in a manner that can be measured and said number is recorded on said

object along with a time stamp when said reading occurs.

50. (Currently amended) The method of claim 49, wherein a subsequent reading of said sample

is used to determine whether a negative-degeneration has occurred for said sample, thereby said

negative-degeneration indicating that a tampering has occurred to said sample.

51. (Previously presented) The method of claim 1, wherein a plurality of samples  $S_i$ , i > 1, is

attached to said object, each said sample S<sub>i</sub> being associated with a corresponding number n<sub>i</sub>

obtained by reading said sample S<sub>i</sub> using a reader of a specific sort; and

recording each number n<sub>i</sub> on at least one of said first recording support and said second

recording support on said object as a pair (S<sub>i</sub>, n<sub>i</sub>),

wherein said object is used as a payment card and a pair (S<sub>i</sub>, n<sub>i</sub>) is destroyed by a reader

for purpose of making a unit payment.

52. (Previously presented) A method of guaranteeing authenticity of an object, said method

comprising:

attaching at least one recording support to said object;

attaching to said object a first sample of material obtainable by at least one of a chemical

process and a physical process having a characteristic that samples generated by said process are

random and non-reproducible, said first sample being associated with a first number obtained by

S/N 09/397,503

a first reading of said first sample using a first reader of a specific sort, wherein said first number

cannot reliably be repeated exactly during a subsequent reading by a reader of said specific sort;

extracting from said first reading an information for a second number, said second

number being reliably repeatable during said subsequent reading;

encoding said second number using an encryption scheme; and

recording, on one of said at least one recording support attached to said object, said

encoding of said second number.

53. (Previously presented) The method of claim 52, further comprising:

recording at least one of said first number and said second number on one of said at least

one recording support attached to said object.

S/N 09/397,503